



300-415^{Q&As}

Implementing Cisco SD-WAN Solutions (ENSDWI)

Pass Cisco 300-415 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/300-415.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which policy blocks TLOCs from remotes and allows TLOCs from the data center to form hub-and-spoke peering?

- A. localized control policy
- B. localized data policy
- C. centralized data policy
- D. centralized control policy

Correct Answer: C

QUESTION 2

In a Cisco SD-WAN architecture, what is the role of the WAN Edge?

- A. It provides orchestration to assist in automatic provisioning of WAN Edge routers and overlay
- B. It is the management plane responsible for centralized configuration and monitoring
- C. It is the control plane that builds and maintains network topology
- D. It is the data plane that is responsible for forwarding traffic

Correct Answer: D

<https://www.cisco.com/c/dam/en/us/solutions/collateral/enterprise-networks/sd-wan/nb-06-cisco-sd-wan-ebook-cte-en.pdf>

QUESTION 3



PEER TYPE	PEER PROTOCOL	PEER SYSTEM IP	SITE ID	DOMAIN ID	PEER PRIVATE IP	PEER PRIVATE PORT
vsmart	dtls	10.1.1.8	1	0	1.1.1.1	12447
vmanage	dtls	10.1.1.7	1	1	2.2.2.2	12647
vmanage	dtls	10.1.1.7	1	1	2.2.2.2	12867
LOCAL						
LOCAL COLOR	STATE	ERROR	ERROR	UNIT		
gold	up	LISFD	NOERR	45		
gold	up	LISFD	NOERR	70		
gold	up	LISFD	NOERR	69		

Refer to the exhibit. An engineer is troubleshooting a control connection issue on a WAN Edge device that shows socket errors. The packet capture shows some ICMP packets dropped between the two devices. Which action resolves the issue?

- A. Remove IP duplication in the network and configure a unique IP address.
- B. Recover vBond or wait for the controller to reload, which could be caused by a reset.
- C. Recover the vManage controller that is down in a high availability cluster.
- D. Change the system IP or restart the WAN Edge if the system IP is changed.

Correct Answer: A

QUESTION 4

An enterprise deployed a Cisco SD-WAN solution with hub-and-spoke topology using MPLS as the preferred network over the Internet. A network engineer must implement an application-aware routing policy to allow ICMP traffic to be load-balanced over both the available links. Which configuration meets the requirement?



- A. **app-route-policy_VPN_10_AAR**
vpn-list VPN_50
sequence 21
match
app-list ICMP
source-ip 0.0.0.0/0
!
action
sla-class ICMP_SLA preferred-color mpls public-Internet
- B. **app-route-policy_VPN_10_AAR**
vpn-list VPN_50
sequence 21
match
app-list ICMP
source-ip 0.0.0.0/0
!
action
sla-class ICMP_SLA
- C. **app-route-policy_VPN_10_AAR**
vpn-list VPN_50
sequence 21
match
app-list ICMP
source-ip 0.0.0.0/0
!
action
sla-class ICMP_SLA preferred-color mpls
backup-sla-preferred-color public-internet
- D. **app-route-policy_VPN_10_AAR**
vpn-list VPN_50
sequence 21
match
app-list ICMP
source-ip 0.0.0.0/0
!
action
sla-class ICMP_SLA preferred-color public-internet
sla-class ICMP_SLA preferred-color mpls




- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: C

QUESTION 5

A company must avoid downtime at the remote sites and data plane to continue forwarding traffic between WAN Edge devices if the branch router loses connectivity to its OMP peers. Which configuration meets the requirement?

A. 

Feature	Value
Graceful Restart for OMP	On
Overlay AS Number	1
Graceful Restart Timer (seconds)	43200
Number of Paths Advertised per Prefix	2
ECMP Limit	4
Shutdown	No



B. CONFIGURATION | TEMPLATES

Device Feature

Feature Template > Add Template > OMP

Basic Configuration Timers Advertise

Graceful Restart for OMP	<input type="radio"/> On <input checked="" type="radio"/> Off
Overlay AS Number	<input type="text" value="2"/>
Graceful Restart Timer (seconds)	<input type="text" value="300"/>
Number of Paths Advertised per Prefix	<input type="text" value="2"/>
ECMP Limit	<input type="text" value="2"/>
Shutdown	<input type="radio"/> Yes <input checked="" type="radio"/> No

C. CONFIGURATION | TEMPLATES

Device Feature

Feature Template > Add Template > OMP

Basic Configuration Timers Advertise

Graceful Restart for OMP	<input checked="" type="radio"/> On <input type="radio"/> Off
Overlay AS Number	<input type="text" value="1"/>
Graceful Restart Timer (seconds)	<input type="text" value="43200"/>
Number of Paths Advertised per Prefix	<input type="text" value="2"/>
ECMP Limit	<input type="text" value="2"/>
Shutdown	<input checked="" type="radio"/> Yes <input type="radio"/> No

D. CONFIGURATION | TEMPLATES

Device Feature

Feature Template > Add Template > OMP

Basic Configuration Timers Advertise

Graceful Restart for OMP	<input type="radio"/> On <input checked="" type="radio"/> Off
Overlay AS Number	<input type="text" value="1"/>
Graceful Restart Timer (seconds)	<input type="text" value="33200"/>
Number of Paths Advertised per Prefix	<input type="text" value="2"/>
ECMP Limit	<input type="text" value="2"/>
Shutdown	<input type="radio"/> Yes <input checked="" type="radio"/> No



- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: A

QUESTION 6

Which two resource data types are used to collect information for monitoring using REST API in Cisco SD-WAN?
(Choose two.)

- A. POST
- B. PUT
- C. scalar
- D. array
- E. DELETE

Correct Answer: CD

QUESTION 7

What is the maximum number of IPsec SAs that are temporarily created and converged on a new set of IPsec SAs in the pairwise keys process during a simultaneous rekey?

- A. 2
- B. 4
- C. 6
- D. 8

Correct Answer: B

QUESTION 8

In the Cisco SD-WAN solution, vSmart controller is responsible for which two actions? (Choose two)



- A. Authenticate and authorize vEdge routers.
- B. Distribute the IP address from DHCP server to vEdge routers
- C. Distribute crypto key information among vEdge routers
- D. Configure and monitor vEdge routers
- E. Distribute route and policy information via OMP.

Correct Answer: CE

QUESTION 9

Which hardware component is involved in the Cisco SD-WAN authentication process for ISR platforms?

- A. ZTP
- B. OTPC
- C. SUDI
- D. TPMD

Correct Answer: C

Reference: <https://www.cisco.com/c/dam/en/us/td/docs/solutions/CVD/SDWAN/sdwan-wan-edge-onboarding-deploy-guide-2020nov.pdf>

QUESTION 10

Which component is used for stateful inspection of TCP, UDP, and ICMP flows in Cisco SD-WAN firewall policies?

- A. zones
- B. sites
- C. subnets
- D. interfaces

Correct Answer: A

QUESTION 11

Which two criteria are supported to filter traffic on a Cisco Umbrella Cloud-delivered firewall? (Choose two.)

- A. geolocation
- B. site ID



C. URL

D. protocol

E. tunnels

Correct Answer: DE

QUESTION 12

Which behavior describes a WAN Edge router running dual DIA when its DPI engine has identified a cloud SaaS application?

A. The gateway WAN Edge router DPI engine accepts the DNS query for SaaS applications, and DNS queries for noncloud applications follow the explicit path.

B. The WAN Edge DPI engine never selects a subperforming DIA circuit for the first application, and the WAN Edge router finds the SaaS application.

C. Existing flows change the path and drop the traffic when the performance of the chosen path degrades.

D. Application traffic flows are routed over best performing DIA circuit, which makes the routing decision based on the best performing path.

Correct Answer: D

QUESTION 13

DRAG DROP

Drag and drop the devices from the left into order on the right to upgrade the software from version 19 to version 20.

Select and Place:



WAN Edge	1
vBond	2
vManager	3
vSmart	4

Correct Answer:

	vManager
	vBond
	vSmart
	WAN Edge

[Latest 300-415 Dumps](#)

[300-415 VCE Dumps](#)

[300-415 Exam Questions](#)