



700-905^{Q&As}

Cisco HyperFlex for Systems Engineers

Pass Cisco 700-905 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/700-905.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which version of HXDP was the first to support multiple VICs on a single server?

- A. HXDP 3.5.1
- B. HXDP 3.0
- C. HXDP 4.0
- D. HXDP 3.5

Correct Answer: A

QUESTION 2

Which two processes does failure on a node initiate? (Choose two.)

- A. Distributed pooled data is migrated off nodes to master data store.
- B. Affected node is marked as unhealthy and placed into standby mode
- C. A call-home process is initiated and the failure is reported to TAC
- D. The VMs on the failed node are moved to another node by vSphere high availability
- E. The system is marked unhealthy but remains operational.

Correct Answer: DE

QUESTION 3

Which two results are expected when you replace a node or expand a cluster? (Choose two.)

- A. Distributed pooled data is migrated off nodes to master data store.
- B. Affected node is marked as unhealthy and placed into standby mode
- C. vSphere DRS migrates the virtual machines to the new node to balance the load
- D. On node replace, the self-healing must finish for the cluster to be healthy
- E. The cluster profile is updated and RAID takes care of rebalancing the load.

Correct Answer: CD



QUESTION 4

HyperFlex virtual servers differ from regular servers in which two key areas? (Choose two.)

- A. NVMe: Regular servers do not support NVMe drives for high availability.
- B. No RAID is required to consolidate disks into a shared data platform.
- C. CVM: Virtual appliance, which performs reading/writing, caching, deduplication, and compression.
- D. SP: UCS Service Profiles are used to delineate MAC address pools from upstream networks.
- E. CCC: Cisco Cloud Center is used for multi-cloud integration and seamless deployment.

Correct Answer: BC

QUESTION 5

What is required to cluster a pair of Fabric Interconnects?

- A. uplink connections to the enterprise network
- B. HXDP 3.5.2 or better
- C. connection between the FI pair using ports L1 and L2
- D. UCS Manager 2.1 or better

Correct Answer: C

QUESTION 6

Which three additional management tools are included in HXDP to configure HyperFlex clusters? (Choose three.)

- A. UCS Manager
- B. Storage CLI
- C. Data Center Network Manager
- D. Cisco IMC 13
- E. REST API
- F. HyperFlex Connect

Correct Answer: BEF

**QUESTION 7**

When local writing or reading is performed, the IOVisor intercepts the read/write requests and forwards them to CVMs across the cluster. This action allows non-local CVMs to be aware of the input/output requests so that they can perform the appropriate input/output action. IOVisor provides which two additional functionalities? (Choose two.)

- A. provides redundancy when local CVM fails, offloading data processing to another CVM in the cluster
- B. when an IOVisor fails, the CVM remains active and functional, which enables uninterrupted operation of the system by forwarding IO to another available IOVisor in the HyperFlex cluster
- C. enables asynchronous replication of data across individual HyperFlex nodes with sub-second re-convergence
- D. integration point for deployment of cloud-based SaaS offerings from eco-system partners
- E. intercepts local virtual machines' reads and writes and distributes them across the network eliminating hotspots

Correct Answer: AE

QUESTION 8

Which three capabilities are provided by Virtual Interface Cards? (Choose three.)

- A. Virtualizing object storage environments by pushing meta data directly to the management server
- B. The virtual interfaces created by a VIC do not accommodate hypervisor communication like VMkernel interfaces on vSphere.
- C. Management through Cisco IMC or UCS Manager with dynamic configuration of virtual interface cards based on the server profile (MAC/WWN).
- D. Traffic processing for internal and external communication supporting simultaneous HBA and NIC operation on the same physical hardware.
- E. Multiple-interface-card virtualization without any additional driver requirements with integration of the virtualized cards into the Fabric Interconnect infrastructure.
- F. A virtual environment, such as VMware vSphere, provides VM connectivity via a virtual switch to individual virtual machines bypassing local hardware requests.

Correct Answer: CDE

QUESTION 9

How can the maximum I/O performance be achieved?



- A. Use the HX 220 with all flash drives
- B. Use the HX 240 with all flash drives
- C. Use the HX 220 with all SAS drives
- D. Use the HX 240 with all SAS drives

Correct Answer: B

QUESTION 10

In all HX server types, where are capacity drives installed?

- A. side
- B. top
- C. back
- D. front

Correct Answer: D

QUESTION 11

Which two steps should be performed before installing HyperFlex? (Choose two.)

- A. Determine and download recommended installer OVA version required
- B. Complete the pre-installation checklist.
- C. Determine and download recommended hypervisor
- D. Download service profile templates
- E. Determine and download virtual machine OS! required

Correct Answer: AB

QUESTION 12

What is the minimum amount of memory required for an HX node?

- A. 192 GB
- B. 64 GB



C. 32 GB

D. 128 GB

Correct Answer: D

QUESTION 13

HyperFlex compute nodes contribute what percentage of the overall disk storage capacity?

A. 5%

B. 20%

C. 0%

D. 10%

Correct Answer: C

[700-905 VCE Dumps](#)

[700-905 Study Guide](#)

[700-905 Braindumps](#)